

DT-805

Mini Sound Level Meter

The DT-805 is a compact sound level meter with dynamic measurement capability of 30 to 130dB; this is covered by 2 ranges of 30 to 100dB and 60 to 130dB. Frequency weighting has both A and C, time constant response is also selectable as either Fast or Slow. This is an easy to use type 2 sound level meter with basic functionality; it also includes a display back light for those low light applications along with a display hold function.

Features

- ◆ Provides 1.4dB accuracy
- ◆ Meets IEC61672-1 Type 2
- ◆ Display Back Light
- ◆ High Performance
- ◆ Max Hold and Data Hold Function

Specifications

Level Range	Low= 30~100dB High= 60~130dB
Accuracy	±1.4dB (ref 94dB @ 1kHz)
Frequency Range	31.5Hz to 8kHz
Frequency Weighting	A, C
Time Weighing	Fast, Slow
Battery Type	9V Battery NEDA 1604, IEC 6F22, JIS 006P
Operation Temp	0°C~40°C (<80%R.H.)
Storage Temp	-10°C~60°C (<70%R.H.)

1.4dB Accuracy

Level range: 30~130dB

Size(HxWxD):

210mm 55mm x 32mm

Weight: 230g



Contact us

South Australia
257 Grange Road
FINDON, SA 5023
P: +61 08 8243 3500
F: +61 08 8243 3501
E: sales@wavecom.com.au

Victoria
772A Station Street,
Box Hill, VIC 3128
P: +61 03 9897 4711
F: +61 03 9897 4766
E: salesvic@wavecom.com.au

Distributed By

