

DIGITAL CONTROL DC POWER SUPPLY PS-3010D-3C



The Wavecom PS-3010D-3C is a high quality 3 Channel Digital Power Supply.

It is a constant voltage and constant current with series and parallel functions e.g. this power supply can be configured in series mode to provide 0-60 VDC @ 5A or it can be configured to provide 0-30 VDC @ 20A. There is also a third channel that supplies 5 VDC @ 3A.

This power supply unit comes with overload, short circuit and overheating protection which meets all industry needs such as defence, development laboratory, heavy industry, training and production applications.

Features

- Constant Voltage
- Constant Current
- Very Low Noise and Ripple
- Short Circuit Protection
- Overload Protection & Reverse Polarity Protection
- Independent Series and Parallel Operation

- Adjustable Current Limit
- 0-30 VDC @ 10A x 2 channels & 30DC @ 3A

vist our web page www.wavecom.com.au



SPECIFICATIONS POWER SUPPLY PS-3010D-3C

Function	Voltage Range o-30V	Current Range o-10A
Load Regulation	≤ 0.01% + 5mv	≤ 0.2% + 5mA
Line Regulation	≤ 0.01% + 2mv	≤ 0.2% + 2mA
Input Voltage	207-253V AC (50Hz)	
Setup Accuracy (25°C + 5°C)	≤ 0.5% + 20mV	≤ 0.5% + 5mA
Ripple and Noise	≤ 1mV Rms	≤ 6mA Rms
Temp. Coefficient	≤ 100ppm + 10mV	≤ 100ppm + 5mA
Protection	Constant Current or Short Circuit Protection	
Read Back Temp. Coefficient	≤ 100ppm + 10mV	≤ 100ppm + 5mA
Voltage Indication Accuracy	LED <u>+</u> 1% + 2 digits	
Operation Environment	Indoor use, Altitude: ≤ 2000m Ambient temperature 0-40°C Relative humidity ≤ 80%	
Interfaces	N/A	N/A
Accessories	User manual, Power cord (1.2M)	
Dimension	365(W)x265(H)x144(D)	
Storage Environment	Ambient temperature—10°C—70°C Relative humidity ≤ 70%	

Order Information

Power Supply Part No: WCM—PS-3010D--3C

Contact us

South Australia 257 Grange Road FINDON, SA 5023P: +61 08 8243 3500
F: +61 08 8243 3501
E: sales@wavecom.com.au

Victoria
772A Station Street,
Box Hill, VIC 3128
P: +61 03 9897 4711
F: +61 03 9897 4766
E: salesvic@wavecom.com.au

