

# Wavecom Instruments

# PS-3005D

## Power Supply Unit



### Contact us

**South Australia**  
257 Grange Road  
Findon, SA 5023  
P: +61 08 8243 3500  
F: +61 08 8243 3501  
E: sales@wavecom.com.au

**Victoria**  
Suite 8, 79-83 High Street,  
Kew, VIC 3101  
P: +61 03 9897 4711  
F: +61 08 8243 3501  
E: sales@wavecom.com.au

**Western Australia**  
Unit 2/17 Casino Street,  
Welshpool, WA 6016  
P: +61 08 9353 1943  
F: +61 08 9353 4319  
E: saleswa@wavecom.com.au

### Distributed By



## Overview

The Wavecom PS-3005D regulated Power Supply is the most economical in the market and has more precision and stability than most units.

The PS-3005D provides constant-voltage and constant-current Power Supply with low ripple and noise, has high reliability and high accuracy. This unit comes with overload, short circuit & overheating protection which meets the needs of development, laboratory, training and production applications.

Potential applications vary from simple school laboratories or personal use, to industrial level R & D, Quality Control and Inspection.

## Features

- ◇ 10 mV / 1 mA resolution
- ◇ Low noise and ripple
- ◇ CV / CC constant voltage & constant current modes
- ◇ Settable OCP & OVP, constant protection mode
- ◇ 5 Sets of parameters can be stored and recalled
- ◇ Output switch control
- ◇ Power-off memory function
- ◇ Keyboard lock function to prevent operator errors

## Contents

- ◇ PS-3005D Power Supply Unit
- ◇ User manual
- ◇ Power cord (1.2M)

### Contact us

**South Australia**  
257 Grange Road  
Findon, SA 5023  
P: +61 08 8243 3500  
F: +61 08 8243 3501  
E: sales@wavecom.com.au

**Victoria**  
Suite 8, 79-83 High Street,  
Kew, VIC 3101  
P: +61 03 9897 4711  
F: +61 08 8243 3501  
E: sales@wavecom.com.au

**Western Australia**  
Unit 2/17 Casino Street,  
Welshpool, WA 6016  
P: +61 08 9353 1943  
F: +61 08 9353 4319  
E: saleswa@wavecom.com.au

### Distributed By

## Specifications

Function	Voltage Range (0V -30V)	Current Range (0A - 5A)
Input Voltage	110V/240V AC	-
Load Regulation	$\leq 0.01\% + 2\text{mV}$	$\leq 0.1\% + 5\text{mA}$
Line Regulation	$\leq 0.01\% + 3\text{mV}$	$\leq 0.1\% + 3\text{mA}$
Setup Resolution	10mV	1mA
Setup Accuracy (25°C + 5°C)	$\leq 0.5\% + 20\text{mV}$	$\leq 0.5\% + 10\text{mA}$
Ripple (20Hz - 20MHz)	2mV RMS	5mA RMS
Temperature Coefficient	$\leq 100\text{ppm} + 10\text{mV}$	$\leq 100\text{ppm} + 5\text{mA}$
Read Back Accuracy	10mV	1mA
Reaction Time	$\leq 100\text{mS}$	$\leq 100\text{mS}$
Operation Environment	Indoor Use Only - Altitude $\leq 2000\text{m}$ Ambient Temperature 0°C - 40°C - Relative Humidity $\leq 80\%$	
Interfaces	N/A - for Programmable Interface Options, see the PS-3005P	
Weight/Dimensions	4.5kg - 110mm x 156mm x 260mm	
Storage Environment	Ambient Temperature -10°C - 70°C - Relative Humidity $\leq 70\%$	

## Ordering Information

◇ Wavecom PS-3005D Power Supply Unit

'WCM-PS3005D'

### Contact us

**South Australia**  
257 Grange Road  
Findon, SA 5023  
P: +61 08 8243 3500  
F: +61 08 8243 3501  
E: sales@wavecom.com.au

**Victoria**  
Suite 8, 79-83 High Street,  
Kew, VIC 3101  
P: +61 03 9897 4711  
F: +61 08 8243 3501  
E: sales@wavecom.com.au

**Western Australia**  
Unit 2/17 Casino Street,  
Welshpool, WA 6016  
P: +61 08 9353 1943  
F: +61 08 9353 4319  
E: saleswa@wavecom.com.au

### Distributed By