



General

Operating temp. & humidity	0°~40°C, 80% Max.
Storage temp. & humidity	-10°~50°C, 80% Max.
Safety standard	EN 61326-1 EN 55011 EN 61000-4-2 EN 61000-4-3
Accessories	Instruction manual Soft pouch Batteries

180 CB

Amplifier Probe (180 CB-A 181 CB A)

- The Amplifier Probe is designed to identify and trace wires or cables within a group without damaging the insulation.
- Works with any Tone Generator to identify wires.
- Volume control for increased sensitivity and adjustable to suit work environment.
- Recessed ON/OFF button prevents battery drain.
- A phone jack is designed for headset or handset.

Frequency	1Hz~12kHz
Receiver distance	< 50cm
Sensitivity control	√
Probe tip	Fixed
Power source	9V(6F22) × 1
Dimensions	230(L) × 56(W) × 27(D)mm
Weight	Approx. 125g (battery included)

Tone Generator (180 CB-G)

- Tone Generator is a great tool for locating and identifying cable pairs or individual conductors.
- 180 CB-G doesn't only provide the function of a tone generator, but also serves as a continuity and polarity tester.
- Test results are displayed by a bi-colored LED.

Over voltage protection	100V DC
Single tone	√
Alternating tone	Fast
Connection	RJ11 connector, alligator clip x 2, RJ45 connector (optional)
Power source	9V(6F22) × 1
Dimensions	64(L)×58(W)×34(D)mm
Weight (battery included)	Approx. 120g

Wave from	Square Wave
Frequency	1kHz±15%