



2330 LX

FEATURES

- Wide range for measurements up 40000 lux and 4000 fc.
- 0.01 lux and 0.001 fc resolution for accurate low light level measurements.
- Light sensor cover is included for preserving sensor life.
- Auto off function.
- Data hold and peak hold function.
- Low battery indication.
- Over range indication.
- Auto-ranged.
- Manual-ranged.
- Calibration mode is provided.
- 9V battery system.
- Selection key for lux and fc.
- The spectral sensitivity close to CIE photopic curve.
- Ideal tool for workplace, clean-room and computer room light testing.
- Video, photographic, office, classroom, and architectural uses.

SPECIFICATIONS

Measuring ranges	39.99 / 399.9 / 3999 / 39990 lux 3.999 / 39.99 / 399.9 / 3999fc
Resolution	0.01 lux - 10 lux 0.001 fc - 1 fc ±(3%rdg+5dgt)
Accuracy	Calibrated to standard incandescent lamp, 2856°K.
Display	4000 count LCD
Photo sensor	Silicon photodiode
Operating / storage conditions	0°C - 40°C < 80 % R.H. -10°C - 50°C < 80 % R.H.
Dimensions	194(L) x 62(W) x 34(D)mm
Weight (battery included)	Approx. 245g
Power source	9V(6F22) × 1
Safety standard	EN 61326-1
Accessories	Instruction manual Carry case Battery